according to Regulation (EC) No. 1907/2006

Ambicat™ LE4476

Version 19.1 Revision Date: 12.11.2024 Former date: 24.04.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Ambicat LE4476

Unique Formula Identifier

(UFI)

: DTW1-UT2J-TD3M-6UXW

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Raw material for plastics industry

Substance/Mixture

1.3 Details of the supplier of the safety data sheet

Supplier : Borealis AG

Trabrennstrasse 6-8, 1020 Vienna, Austria

Telephone: +43 1 22400 0

E-mail address : sds@borealisgroup.com

1.4 Emergency telephone number

+1 760 476 3962 (3E), Access code: 336296

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Reproductive toxicity, Category 2 H361d: Suspected of damaging the unborn child.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :

Signal word : Warning

Hazard statements : H361d Suspected of damaging the unborn child.

Precautionary statements : Prevention:

Ambicat is a trademark of the Borealis group.



Borealis AG | Trabrennstrasse 6-8 | 1020 Vienna | Austria

according to Regulation (EC) No. 1907/2006

Ambicat LE4476

Version 19.1 Revision Date: 12.11.2024 Former date: 24.04.2024

P201 Obtain special instructions before use.

P280 Wear protective gloves.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Hazardous components which must be listed on the label:

Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

The product burns, but is not classified as flammable.

During crosslinking reaction in combination with base resin: methanol (Flam. Liq. 2; H225, Acute Tox. 3; H301, Acute Tox. 3; H311, Acute Tox. 3; H331, STOT SE 1; H370) is released.

In contact with water or moisture methanol will be released.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : The product is a silane crosslinkable polyethylene copolymer.

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
Phenol, 4-methyl-, reaction	68610-51-5	Repr. 2; H361d	>= 3 - < 10
products with dicyclopentadiene	271-867-2	Aquatic Chronic 4;	
and isobutylene	01-2119496062-39	H413	
Benzenesulfonic acid, 4-C10-13-	85536-14-7	Acute Tox. 4; H302	>= 1 - < 2,5



according to Regulation (EC) No. 1907/2006

Ambicat LE4476

Version 19.1 Revision Date: 12.11.2024 Former date: 24.04.2024

sec-alkyl derivs.	287-494-3	Skin Corr. 1C; H314	
	01-2119490234-40	Eye Dam. 1; H318	
		Aquatic Chronic 3;	
		H412	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Move to fresh air.

Seek medical advice immediately.

In case of skin contact : If molten material comes in contact with the skin, cool with

plenty of water. DO NOT remove solidified product, as

removal could result in severe tissue damage.

Obtain medical attention.

Wash off with soap and plenty of water.

Call a physician if irritation develops or persists.

In case of eye contact : Rinse thoroughly with plenty of water, also under the eyelids.

Get medical attention if irritation develops and persists.

If swallowed : If swallowed, rinse mouth with water (only if the person is

conscious).

Seek medical advice immediately.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation of dust may irritate the respiratory tract.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

Symptoms of poisoning (methanol):

Daze Dizziness Nausea Abdominal pain

Abdominal pain Respiratory disorders

Symptoms of poisoning, prolonged exposure (methanol):

Blindness



according to Regulation (EC) No. 1907/2006

Ambicat LE4476

Version 19.1 Revision Date: 12.11.2024 Former date: 24.04.2024

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water in spread jet, dry chemicals, foam or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Principal toxicant in the smoke is carbon monoxide.

5.3 Advice for firefighters

for firefighters

Special protective equipment : Wear self-contained breathing apparatus and protective suit.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Use personal protective equipment.

6.2 Environmental precautions

Should not be released into the environment.

It is recommended to implement systems and practices (such as Operation Clean Sweep®) to prevent accidental release of plastics in to the environment.

6.3 Methods and material for containment and cleaning up

Vacuum or sweep up spill.

All spill of material must be removed immediately to prevent slipping accidents.

Do not flush into surface water or sanitary sewer system.

Dispose of in accordance with local regulations.

6.4 Reference to other sections

For personal protection see section 8.

For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : During processing and thermal treatment of the product, small

amounts of volatile hydrocarbons may be released.



according to Regulation (EC) No. 1907/2006

Ambicat LE4476

Version 19.1 Revision Date: 12.11.2024 Former date: 24.04.2024

Provide adequate ventilation.

Local exhaust ventilation may be necessary. Avoid inhalation of dust and decomposition fumes.

Avoid contact with skin and eyes.

Advice on protection against

fire and explosion

: Dust from the product gives a potential risk for dust explosion.
All equipment shall be grounded. Routine housekeeping

should be instituted to ensure that dusts do not accumulate on

surfaces.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. Wash hands before breaks and at the end of

workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

: Store in a place accessible by authorized persons only.

Further information on

storage stability

: Keep in a dry place.

7.3 Specific end use(s)

Specific use(s) : Raw material for wire and cable applications.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

For national exposure limit (OEL) values, check country specific safety data sheets.

Occupational exposure limits of decomposition products

•		•		
Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
methanol	67-56-1	TWA	200 ppm 260 mg/m3	2006/15/EC
Further information	Indicative, Identifies the possibility of significant uptake through the skin			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene	Workers	Oral	Long-term exposure	0,8 mg/kg
Remarks:	Exposure time: 24 hrs			
	Workers	Dermal	Long-term exposure	4 mg/kg
Remarks:	Exposure time: 24 hrs			
	Workers	Inhalation	Long-term exposure	0,35 mg/m3
Benzenesulfonic acid,	Workers	Skin contact	Long-term systemic	170 mg/kg



according to Regulation (EC) No. 1907/2006

Ambicat LE4476

Version 19.1 Revision Date: 12.11.2024 Former date: 24.04.2024

4-C10-13-sec-alkyl derivs.			effects	bw/d
	Workers	Inhalation	Long-term systemic effects, Long-term local effects	12 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Phenol, 4-methyl-, reaction	Sewage treatment plant	150,9 mg/l
products with dicyclopentadiene		
and isobutylene		

8.2 Exposure controls

Engineering measures

Provide adequate ventilation.

Local exhaust ventilation may be necessary.

Personal protective equipment

Eye protection : No special protective equipment required.

However, it is recommended to use eye protection according

to EN 166.

Hand protection

Material : Wear suitable gloves:

Remarks : Please observe the instructions regarding permeability and

breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the

danger of cuts, abrasion, and the contact time.

Protective gloves complying with EN 374.

Skin and body protection : No special protective equipment required.

Respiratory protection : In case of insufficient ventilation: Respirator with ABEK-P3

filter or self-contained breathing apparatus. In case of dust development use dust mask.

Protective measures : Appropriate personal protective equipment (PPE) shall be

worn in accordance with Regulation (EU) 2016/425.

Environmental exposure controls

General advice : Should not be released into the environment.

It is recommended to implement systems and practices (such as Operation Clean Sweep®) to prevent accidental release of

plastics in to the environment.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties



according to Regulation (EC) No. 1907/2006

Ambicat LE4476

Version 19.1 Revision Date: 12.11.2024 Former date: 24.04.2024

Physical state : pellets
Colour : beige
Odour : acrylic-like
Odour Threshold : Methanol:

Do NOT rely on the odour: olfactory level is above the

exposure limit.

Melting point/range : 100 - 140 °C

Boiling range : Not applicable

Decomposes below the boiling point.

Flammability : The product is not flammable.

Upper explosion limit / Upper

flammability limit

Not applicable

Lower explosion limit / Lower :

flammability limit

Not applicable

Flash point : Not applicable, (solid)

Auto-ignition temperature : > 320 °C

pH : Not applicable insoluble

Viscosity

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

Not applicable

(solid)

Vapour pressure : Not applicable

(solid)

Density : 0,9 - 1,0 g/cm³

Particle size : 3 - 10 mm

Method: Image analysis (surface-based)

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.



according to Regulation (EC) No. 1907/2006

Ambicat LE4476

Version 19.1 Revision Date: 12.11.2024 Former date: 24.04.2024

Evaporation rate : Not applicable

(solid)

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.

10.2 Chemical stability

The product is a stable thermoplastic.

The intended crosslinking reaction occurs in combination with the base resin and moisture: at ambient conditions, in sauna or hot water bath.

10.3 Possibility of hazardous reactions

Hazardous reactions : In contact with water or moisture methanol will be released.

10.4 Conditions to avoid

Conditions to avoid : Never allow product to get in contact with water during

storage.

10.5 Incompatible materials

Materials to avoid : None known.

10.6 Hazardous decomposition products

Under fire conditions: carbon monoxide

During processing and thermal treatment of the product, small amounts of volatile hydrocarbons may be released.

During crosslinking reaction in combination with base resin: methanol

In contact with water or moisture methanol will be released.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Components:

Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.:

Acute oral toxicity : LD50 (Rat): 1.470 mg/kg

Method: OECD Test Guideline 401



according to Regulation (EC) No. 1907/2006

Ambicat LE4476

Version 19.1 Revision Date: 12.11.2024 Former date: 24.04.2024

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 402 Remarks: Read-across (Analogy)

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Product:

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 439

Result : No skin irritation

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Product:

Species : Bovine cornea

Method : OECD Test Guideline 437

Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Suspected of damaging the unborn child.

Components:

Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene:

Effects on fertility : Test Type: Pre-/postnatal development

Species: Rabbit, female Application Route: Oral

Dose: 50 mg/kg

Method: OECD Test Guideline 414

Result: Some evidence of adverse effects on development,

based on animal experiments.

GLP: yes



according to Regulation (EC) No. 1907/2006

Ambicat LE4476

Version 19.1 Revision Date: 12.11.2024 Former date: 24.04.2024

STOT - single exposure

Based on available data, the classification criteria are not met.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Aspiration toxicity

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain components

> considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Further information

Product:

Remarks During crosslinking reaction in combination with base resin:

> methanol (Flam. Liq. 2; H225, Acute Tox. 3; H301, Acute Tox. 3; H311, Acute Tox. 3; H331, STOT SE 1; H370) is released. Methanol: Toxic by inhalation, in contact with skin and if

swallowed.

Inhalation of dust may irritate the respiratory tract.

Remarks Information given is based on tests on the mixture itself.

Information given is based on data of the components.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 0,2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: No effect up to the limit of solubility.

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 0,2 mg/l

Exposure time: 48 h





according to Regulation (EC) No. 1907/2006

Ambicat LE4476

Version 19.1 Revision Date: 12.11.2024 Former date: 24.04.2024

Method: OECD Test Guideline 202

Remarks: No effect up to the limit of solubility.

Toxicity to algae/aquatic

plants

: EC50 (Selenastrum capricornutum (fresh water algae)): > 0,2

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: No effect up to the limit of solubility.

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: Not readily biodegradable.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Does not accumulate in organisms.

12.4 Mobility in soil

Product:

Mobility : Remarks: Not expected to adsorb on soil.

Remarks: The product is insoluble and floats on water.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:



according to Regulation (EC) No. 1907/2006

Ambicat LE4476

Version 19.1 Revision Date: 12.11.2024 Former date: 24.04.2024

Additional ecological

information

: Should not be released into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of contents/ container to an approved waste disposal

plant.

Check with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

SECTION 14: Transport information

14.1 UN number or ID number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Not dangerous goods in the meaning of ADR/RID, ADN,

IMDG-Code, ICAO/IATA-DGR

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture



according to Regulation (EC) No. 1907/2006

Ambicat LE4476

Version 19.1 Revision Date: 12.11.2024 Former date: 24.04.2024

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

15.2 Chemical safety assessment

no

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.

H314 : Causes severe skin burns and eye damage.

H318 : Causes serious eye damage.

H361d : Suspected of damaging the unborn child.
H412 : Harmful to aquatic life with long lasting effects.
H413 : May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage Repr. : Reproductive toxicity Skin Corr. : Skin corrosion

2006/15/EC : Europe. Indicative occupational exposure limit values

2006/15/EC / TWA : Limit Value - eight hours

Further information

Other information : Issued according to Regulation (EC) No 1907/2006, Annex II,

and its amendments.

Changes since the last version are highlighted in the margin.

This version replaces all previous versions.

Issuer : Borealis, Group Product Stewardship

Sources of key data used to

compile the Safety Data

Sheet

The classification information of components is based on raw

material supplier data.

Information given is based on tests on the mixture itself. Information given is based on data of the components.

Classification of the mixture: Classification procedure:

Repr. 2 H361d Calculation method



according to Regulation (EC) No. 1907/2006

Ambicat LE4476

Version 19.1 Revision Date: 12.11.2024 Former date: 24.04.2024

Disclaimer

To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication; however we do not assume any liability whatsoever for the accuracy and completeness of such information.

Borealis makes no warranties which extend beyond the description contained herein. Nothing herein shall constitute any warranty of merchantability or fitness for a particular purpose.

It is the customer's responsibility to inspect and test our products in order to satisfy itself as to the suitability of the products for the customer's particular purpose. The customer is responsible for the appropriate, safe and legal use, processing and handling of our products.

No liability can be accepted in respect of the use of Borealis' products in conjunction with other materials. The information contained herein relates exclusively to our products when not used in conjunction with any third party materials.

